

# FORTE PROFILE 150 HD 20°/40° 3000K BLACK


**Cod. 0913063490**

FIXTURE WITH 1m of CABLE

Handy orientable profiler with a compact size and manual adjustment of zoom and focus, with high-definition optics, 1 COB source with ultra-high light output. Salt mist resistant paint. Anti-condensation valve. Complete with gobo holder.

**Technical data:**

Power supply	100-240 V AC 50/60Hz
Current	0.25 A @230V AC
Maximum power consumption	58W
Electrical insulation class	I
Connection	1 m OF NEOPRENE CABLE 3X1.5
Beam angle	20°/40°
Number of LEDs	1
LED colour	3000K
Colour Rendering	CRI>92
Total luminous flux	5559 lm
Body	ANODIZED ALUMINIUM
Finish colour	PAINTED BLACK
Weight	5.6 kg
IP protection rating	IP65
Working position	ANY
Cooling system	NATURAL CONVECTION
Ambient temperature limits	-20°C/+40°C
Thermal protection	ACTIVE ELECTRONICS
Control signal	ON/OFF



- 1 ALUMINIUM DIE CASTING
- 2 SHUTTERS
- 3 GOBO HOLDER
- 4 ZOOM LENSES
- 5 FOCUS LENS
- 6 IP65 COVERAGE
- 7 ORIENTABLE BRACKET
- 8 ZOOM AND FOCUS TIGHTENING
- 9 ANTI-CONDENSATION VALVE


17/01/24 - The data in this document may be changed without notice in order to improve the product or to correct any errors.

# FORTE PROFILE 150 HD 20°/40° 3000K BLACK

Cod. 0913063490

FIXTURE WITH 1m of CABLE

Handy orientable profiler with a compact size and manual adjustment of zoom and focus, with high-definition optics, 1 COB source with ultra-high light output. Salt mist resistant paint. Anti-condensation valve. Complete with gobo holder.



17/01/24 - The data in this document may be changed without notice in order to improve the product or to correct any errors.